DMS DMGm3101 9990183ec Rev.0

3105854-617

(New model)




| No. | NAME OF PART | QT'Y. | MATERIAL | REMARKS |
|---|---|---|---|---|
| 1 | SINGLE JOINT | 2 | S45C | |
| 2 | SLEEVE FLANGE | 1 | S45C | |
| 3 | SPLINE FLANGE | 1 | S45C SCM435 | |
| 4 | COMPANION FLANGE | 1 | S45C STKM13C | |
| 5 | COMPANION FLANGE | 1 | S45C | |

SPECIFICATION

| | |
|---|---|
| MAX. TRANSMITTABLE TORQUE | :7900N·m (806Kgf·m) |
| ALLOWABLE ANGLE AT OPERATION | :25 DEG. |
| MAX. EXPANTION OF SPLINE | :80mm |
| BOLTS FOR CONNECTING FLANG | :M14×2 |
| FASTENING TORQUE OF BOLTS | :196N·m |

| SYM. | REVISIONS | DATE | REVD. | CHKD. | APPD. | RE. DWG. | NTR | RE. MF. | RE. Q. D. |
|---|---|---|---|---|---|---|---|---|---|
| | | | | | | | | | |

| | | | |
|---|---|---|---|
| DRWN. | K.Sugiura | 99.03.30 | PROJECTION |
| CHKD. | K.Ohgo | 99.03.30 | SCALE NTS |
| APPD. | T.Shimizu | 99.03.30 | |

TITLE: FAN DRIVE UNIVERSAL COUPLING

REV.

Hitachi, Ltd.
Tokyo Japan

DWG. NO. 3105[illegible]4-6

SH.

ENERGY SDN