

DATA SHEET FC

ITEMS	details	
nominal parameter	Rated voltage(V)	24V
	Rated outpower(kW)	3KW
	Rated current(A)	150-170A
	Rate speed(r/min)	2000-2600
duty cycle	S1	60 MIN CONTINIOS
	S2 (min)	
	S3(%)	50% 60 MIN CONT - 60 MIN 088
	other	
operational environment	altitude (m)	1000 meter
	Max ambient temperature (°C)	50C
	(°C) min ambient temperature	-10 C
	relative humidity (%)	100%
others	rotation direction	CCW
	IP class	IP 55
	insulation	500V MORE THEN -10 M OM
	mounting	TOP TANK
	noise	
	vibration	ON VEHICLE
	Excitation mode	PERMANENT MAGNET
	weight(kg) >	MIN
	external diameter (mm)	MAX 130 MM

overall dimension	frame length（mm）	MAX 200 MM
	center height（mm）	
	maximum dimensions(L*W*H)	

OR DC MOTORS

Power supply		
storage battery	8 BATTERES 24V	
application		
hydraulic system	hydraulic system	
flange dimentions requered	out flange 200 m"m with shaft of 24 m	
or	out flange 250 m"m with shaft of 28 m	
Certification requirements		
please we need all documents you can provide.like CE or UL OR others		

--	--	--